

Timbersled® ARO™ 120

Specifications

Drivetrain

Chain Case Chain | EK520 SRX2 52 Link (continuous)

Chain Slider | Standard

Disc Brake Type | Wilwood Hydraulic Dual Piston

Jack Shaft Sprocket | 17 tooth - 15t spline

Lower Chain Case Sprocket | 17 tooth - 15t spline

Track Driver | EK520 SRX2 70 Link (master link)

Upper Chain Case Sprocket | 18 tooth - 15t spline

Dimensions

Estimated Dry Weight - Front (lbs/kg) | 16.0 / 7.25

Estimated Dry Weight - Rear (lbs/kg) | 111.3 / 50.5

Overall Length | 63 in (160 cm)

Suspension

Front Track Shock | FOX® ZERO Pro®

Rear Suspension | Timbersled ARO™ Long Travel

Rear Track Shock | FOX® ZERO Pro®

Rear Travel - Fixed Install Kit (in/cm) | 12 / 30.5

Rear Travel - TSS Install Kit (in/cm) | 20 / 50.8

Skag Type | Timbersled Traverse™ Hardened

Ski Type | Timbersled Traverse Ski™

Track Width / Length / Height (in) | 11.5 x 120 x 2.5 Traverse Track™

Features

Color / Graphics | Black / Blue / Red / Orange / White

Install Kits | Suspension Strut and Fixed Strut

Storage Mat | Accessory

Storage System | Accessory