

Timbersled® ARO™ 129

Specifications

Drivetrain

Chain Case Chain | EK520 SRX2 52 Link (continuous)
Chain Slider | Standard
Disc Brake Type | Wilwood Hydraulic Dual Piston
Drive Chain | EK520 SRX2 70 Link (master link)
Jack Shaft Sprocket | 17 tooth - 15t spline
Lower Chain Case Sprocket | 17 tooth - 15t spline
Master Cylinder | Brembo RH Hydraulic Adjustable
Track Driver | 6 Tooth 2.86 Pitch
Upper Chain Case Sprocket | 18 tooth - 15t spline

Dimensions

Estimated Dry Weight - Front (lbs/kg) | 16.0 / 7.25
Estimated Dry Weight - Rear (lbs/kg) | 117.0 / 53.1
Overall Length - pivot to bumper (in/cm) | 65.5 / 166.37

Suspension

Front Track Shock | Timbersled IFP / FOX ZERO QS3®
Rear Suspension | Timbersled ARO™ Long Travel
Rear Track Shock | Timbersled IFP / FOX ZERO QS3®
Rear Travel - Fixed Install Kit (in/cm) | 12 / 30.5
Rear Travel - TSS Install Kit (in/cm) | 20 / 50.8
Skag Type | Timbersled Traverse™ Hardened
Ski Type | Timbersled Traverse Ski™
Track Width / Length / Height (in) | 11.5 x 129 x 2.5 Traverse Track™

Features

Color / Graphics | Black
Install Kits | ARO Fixed Strut/Suspension Strut
Storage | Accessory
Storage Mat | Accessory

*FOX® is a registered trademark of Fox Factory Inc.