

# **Timbersled® ARO**

## **3™ Specifications**

### **Drivetrain**

Chain Case Chain | EK520 SRX2 52 Link (continuous)  
Chain Slider | Standard  
Disc Brake Type | Wilwood Hydraulic Dual Piston  
Drive Chain | EK520 SRX2 70 Link (master link)  
Jack Shaft Sprocket | 17 tooth - 15t spline  
Lower Chain Case Sprocket | 17 tooth - 15t spline  
Master Cylinder | Brembo RH Hydraulic Adjustable  
Track Driver | 6 Tooth 3.0 Pitch  
Upper Chain Case Sprocket | 18 tooth - 15t spline

### **Dimensions**

Estimated Dry Weight - Front (lbs/kg) | 16.0 / 7.25  
Estimated Dry Weight - Rear (lbs/kg) | 121.0 / 54.9  
Overall Length - pivot to bumper (in/cm) | 65.5 / 166.37

### **Suspension**

Front Track Shock | FOX® ZERO QS3®  
Rear Suspension | Timbersled ARO™ Long Travel  
Rear Track Shock | FOX® ZERO QS3®  
Rear Travel - Fixed Install Kit (in/cm) | 12 / 30.5  
Rear Travel - TSS Install Kit (in/cm) | 20 / 50.8  
Skag Type | Timbersled Traverse™ Hardened  
Ski Type | Timbersled Traverse Ski™  
Track Width / Length / Height (in) | 11.5 x 129 x 3.0 Track

### **Features**

Color / Graphics | Titanium Silver  
Install Kits | ARO Fixed Strut/Suspension Strut  
Storage | Accessory  
Storage Mat | Accessory

\*FOX® is a registered trademark of Fox Factory Inc.